



# A-LINK®

## A-LINK SD8GA

### 8 PORT 10/100/1000Mb SWITCH

A-LINK SD8GA(r), 8-port 10/100/1000MB Switch with MDI-X autosensing ports.

**Product specification :**

• Standards :

IEEE 802.3 10BASE-T  
IEEE 802.3u 100BASE-TX  
IEEE 802.3x  
IEEE 802.3ab 1000BASE-T

• Autosence :

Auto-MDI/MDIX detects and corrects cabling errors.

• MAC address :

4096

• Buffer memory :

1Mb

• Forwarding mode :

Store-and-forward

• Interface :

8 x 10/100/1000 Mbps RJ-45 ports

• Transmission mode :

Half or full duplex

• Protocol :

CSMA/CD

• Uplink :

Shared with 8th port

• Flow control :

Back pressure, IEEE 802.3x

• Panel indicators :

Per unit: power  
Per port: link/activity, 10/100/1000Mb indication

• Output of power adapter :

12V DC, 1.0A

• Compliance :

CE and FCC

• A-LINK Retail package contains :

- Switch  
- Power adapter  
- Installation guides

• Ean / Order code :

- 6418949 026106

A-LINK is a registered trademark of A-Link.  
<http://www.a-link.com> SD8GA specs UK 12.11.08  
All rights reserved